

Maxwell Road
Stevenage
Hertfordshire
SG1 2EW

T: +44(0) 1438 777 700
info@fira.co.uk

www.fira.co.uk

PINEAPPLE CONTRACTS

Westmead
Maidstone
Kent
ME20 6XJ

Our Ref: TSSEF87494
Date: 02 October 2019
Delivery Date: 24 June 2019
Test Dates: 24 June 2019 - 13 August 2019

For the attention of Siuling Leung

SAMPLE(S) SUBMITTED FOR TEST AND IDENTIFIED BY CUSTOMER AS:

One, Rock Chair

TEST(S) AS REQUESTED BY CUSTOMER:

BS EN 16139: 2013 Test Level 2

RESULT:

Pass*

*Excluding Information for Use.

Technical report references marked * indicate this report is supplementary to the previous report with the same reference

FIRA International is a UKAS TESTING Laboratory No. 0174

Tests marked "Not UKAS Accredited" in this Report are not included in the UKAS Accreditation Schedule for our laboratory.

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

This Report relates to the sample(s) submitted for test and no others. Additions, deletions or alterations are not permitted.

Test reports are given to the client in confidence, and may only be reproduced in whole or in part with written permission from FIRA International Limited. Note that the words "**tested by FIRA International**" may be used in subsequent publicity for the product; "approved" must **not** be used.

Tests are carried out on the understanding that neither FIRA International Limited nor its officers can accept any legal responsibility for information or advice given or opinions expressed whether in response to specific enquiries or otherwise. This Report is given subject to the Terms of Business of FIRA International Limited which are available at www.fira.co.uk/images/FIRA-International-Limited-Standard-Terms-of-Business-2018.pdf



TSSEF87494
Page 1 of 9

FIRA International
Registered office: 10 Lower Grosvenor Place,
London, UK, SW1W 0EN
Registered in England No: 3181481

TECHNICAL REPORT

DESCRIPTION

Item: Rock Chair
Supplied by: **PINEAPPLE CONTRACTS**
Number of Photos: One to Four

All dimensions are approximate.

| Quantity | Part Name | Material |
|----------|----------------|------------------|
| 1 | Seat | 10mm Thick Wood |
| 1 | Back | 10mm Thick Wood |
| 4 | Legs | 36mm x 45mm Wood |
| 2 | Sled Base | 25mm Thick Wood |
| | Weight = 6.5kg | |

PRECONDITIONING AND MOISTURE CONTENT

FIRA International cannot validate date of manufacture and therefore it is assumed that at least 4 weeks has elapsed between date of manufacture and delivery to FIRA International.
Unless otherwise stated on the first page of this report the sample was stored in indoor ambient conditions for at least the minimum duration as required by this standard prior to test.
Wherever possible timber moisture content is verified prior to test. Where this is not possible the moisture content is assumed to be in the range 8 – 12 %.



TECHNICAL REPORT

BS EN 16139: 2013 - Furniture – Strength, Durability and Safety – Requirements for Contract Seating

The tests required were carried out in accordance with the standard. Where applicable details of the loads applied and their positions of application are retained at FIRA International and are available on request. Structural testing machines are set to operate at the tolerances stated in the standard. Uncertainty of Measurement calculations have not been applied. FIRA International Uncertainty of Measurement values are available on request.

Item: Rock Chair

Initial Inspection: No apparent faults

| Clause | Test | Result |
|--------|---|--------|
| 4.1 | General requirements (Clause Ref: BS EN 16139: 2013) | |
| a | accessible corners are rounded or chamfered; | Pass |
| b | the edges of the seat, back rest and arm rests which are in contact with the user when sitting in the chair are rounded or chamfered; | Pass |
| c | the edges of handles are rounded or chamfered in the direction of the force applied; | N/A |
| d | all other edges are free from burrs and rounded or chamfered; | Pass |
| e | the ends of hollow components are closed or capped. | N/A |
| | Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided. | N/A |
| | It shall not be possible for any load bearing part of the seating to come loose unintentionally. | Pass |
| | All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use. | N/A |
| 4.2 | Shear and squeeze points | |
| 4.2.1 | Shear and squeeze points when setting up and folding. | N/A |
| 4.2.2 | Shear and squeeze points under influence of powered mechanism. | N/A |
| 4.2.3 | Shear and squeeze points during use. | Pass |

In extreme weather conditions the ambient test temperature and/or humidity may fall outside the requirements of the standard. Such changes have not been shown to affect the validity of the results. Details of the ambient conditions at time of test are available on request.



TECHNICAL REPORT

BS EN 16139: 2013 - Furniture – Strength, Durability and Safety – Requirements for Contract Seating

The tests required were carried out in accordance with the standard. Where applicable details of the loads applied and their positions of application are retained at FIRA International and are available on request. Structural testing machines are set to operate at the tolerances stated in the standard. Uncertainty of Measurement calculations have not been applied. FIRA International Uncertainty of Measurement values are available on request.

Item: Rock Chair

Initial Inspection: No apparent faults

| Clause | Test | Result |
|--------|--|--------|
| 4.3.3 | Stability: non-swivel chairs only (Clause Ref: BS EN 1022: 2005) | |
| 6.2 | Forwards overbalancing, all seating. | Pass |
| 6.3 | Forwards overturning for seating with footrest. | N/A |
| 6.4 | Sideways overbalancing, all seating without arms. | Pass |
| 6.5 | Sideways overbalancing, all seating with arms. | N/A |
| 6.6 | Rearwards overbalancing, all seating with backs. | Pass |
| 7.3 | Tilting chairs. | N/A |
| 7.4 | Rocking chairs. | N/A |
| 7.5 | Reclining chairs with footrest. | N/A |
| 7.7 | Reclining chairs without footrest. | N/A |

| Clause | Test | Result |
|--------|---|--------|
| 4.4 | Rolling resistance of the unloaded chair (Clause Ref: EN 16139: 2013) | |
| a | The rolling resistance is ≥ 12 N when tested according to EN 1335-3:2009, 7.4; | N/A |
| b | All castors are of the same type | N/A |

In extreme weather conditions the ambient test temperature and/or humidity may fall outside the requirements of the standard. Such changes have not been shown to affect the validity of the results. Details of the ambient conditions at time of test are available on request.



TECHNICAL REPORT

BS EN 16139: 2013 - Furniture – Strength, Durability and Safety – Requirements for Contract Seating

The tests required were carried out in accordance with the standard. Where applicable details of the loads applied and their positions of application are retained at FIRA International and are available on request. Structural testing machines are set to operate at the tolerances stated in the standard. Uncertainty of Measurement calculations have not been applied. FIRA International Uncertainty of Measurement values are available on request.

Item: Rock Chair

Initial Inspection: No apparent faults

| Clause | Test | Result |
|--------|---|--------|
| 4.3.2 | Stability: swivel chairs only (Clause Ref: BS EN 1335: 2009) *Clause Ref: 1022: 2005 | |
| 7.1.1 | Front edge overbalancing. | N/A |
| 7.1.2 | Forwards overbalancing. | N/A |
| *6.3 | Forwards overturning for seating with footrest. | N/A |
| 7.1.4 | Sideways overbalancing, all seating without arms. | N/A |
| 7.1.5 | Sideways overbalancing, all seating with arms. | N/A |
| 7.1.6 | Rearwards overturning - without back rest inclination. | N/A |
| 7.1.7 | Rearwards overturning - with back rest inclination. | N/A |

| Clause | Test | Result |
|--------|---|--------------|
| 7 | Information for use (Clause Ref: BS EN 16139: 2013) | |
| a | Information regarding the intended use; | Not Supplied |
| b | If the chair is fitted with adjusting mechanisms: instruction for operating the adjusting mechanisms; | N/A |
| c | Assembly instructions, where applicable; | N/A |
| d | Instruction for care and maintenance of the chair; | Not Supplied |
| e | If the seating is fitted with castors: information on the choice of castors in relation to the floor surface; | N/A |
| f | If the seating is fitted with adjustment mechanisms comprising an energy accumulator, an additional note is required pointing out that only instructed personnel may replace and maintain adjustment mechanisms containing energy accumulators. | N/A |

In extreme weather conditions the ambient test temperature and/or humidity may fall outside the requirements of the standard. Such changes have not been shown to affect the validity of the results. Details of the ambient conditions at time of test are available on request.



TECHNICAL REPORT

BS EN 16139: 2013 - Furniture – Strength, Durability and Safety – Requirements for Contract Seating

The tests required were carried out in accordance with the standard. Where applicable details of the loads applied and their positions of application are retained at FIRA International and are available on request. Structural testing machines are set to operate at the tolerances stated in the standard. Uncertainty of Measurement calculations have not been applied. FIRA International Uncertainty of Measurement values are available on request.

Item: Rock Chair

Initial Inspection: No apparent faults

| Clause | Test | Result |
|-----------------------|--|--------|
| 5.4 | Strength and durability (Clause Ref: BS EN 1728: 2012) | |
| 6.4 | Seat static load test. | Pass |
| 6.4 | Back static load test. | Pass |
| 6.4 | Additional seat static load test. | N/A |
| 6.4 | Additional back static load test. | N/A |
| 6.5 | Seat front edge static load test. | Pass |
| 6.6 | Vertical static load on back. | Pass |
| 6.8 & 6.9 | Foot rest static load test. | N/A |
| 6.10 | Arm rest sideways static load test. | N/A |
| 6.11 | Arm rest downwards static load test. | N/A |
| 6.13.1 & 6.13.2 | Vertical upwards static load on arm rests. | N/A |
| 6.17 | Seat durability test (Seat position 1). | Pass* |
| 6.17 | Seat durability test (Seat position 2). | N/A |
| 6.17 | Back durability test (Back position 1). | Pass* |
| 6.17 | Back durability test (Back position 2). | N/A |
| 6.17 | Additional seat durability test. | N/A |
| 6.17 | Additional back durability test. | N/A |

*Additional 300,000 cycles carried out at the end of standard testing due to customer request.

In extreme weather conditions the ambient test temperature and/or humidity may fall outside the requirements of the standard. Such changes have not been shown to affect the validity of the results. Details of the ambient conditions at time of test are available on request.



TECHNICAL REPORT

BS EN 16139: 2013 - Furniture – Strength, Durability and Safety – Requirements for Contract Seating

The tests required were carried out in accordance with the standard. Where applicable details of the loads applied and their positions of application are retained at FIRA International and are available on request. Structural testing machines are set to operate at the tolerances stated in the standard. Uncertainty of Measurement calculations have not been applied. FIRA International Uncertainty of Measurement values are available on request.

Item: Rock Chair

Initial Inspection: No apparent faults

| Clause | Test | Result |
|--------|---|--------|
| | (Clause Ref: BS EN 1728: 2012) | |
| 6.18 | Seat front edge durability test (ALT). | Pass |
| 6.18 | Seat front edge durability test (SLP). | N/A |
| 6.20 | Arm rest durability test. | N/A |
| 6.21 | Foot rest durability test. | N/A |
| 6.15 | Leg forwards static load test. | Pass |
| 6.16 | Leg sideways static load test. | Pass |
| 6.24 | Seat impact test. | Pass |
| 6.25 | Back impact test. | Pass |
| 6.26 | Arm impact test. | N/A |
| 6.27.1 | Drop test (multiple seating). | N/A |
| 6.14 | Auxiliary writing surface static load test. | N/A |
| 6.22 | Auxiliary writing surface durability test. | N/A |

In extreme weather conditions the ambient test temperature and/or humidity may fall outside the requirements of the standard. Such changes have not been shown to affect the validity of the results. Details of the ambient conditions at time of test are available on request.



TECHNICAL REPORT

CONCLUSION

The Rock Chair, as previously described, successfully satisfied the applicable test requirements of BS EN 16139: 2013 Test Level 2 - Excluding Information for Use.

Tested by: D Lawrence & K Blair

Reported by: G Wright

Approved by: L Haines

Section Head - Structural Testing



TECHNICAL REPORT



Photo 1 - Rock Chair



Photo 2 - Rock Chair



Photo 3 - Rock Chair



Photo 4 - Rock Chair

*****End of Report*****